▼ Shown: Cross-Bearing Puller Set BHP361G



- Precise hydraulic control allows fast, efficient and safe pulling
- High quality, forged steel components provide superior reliability and service
- The Cross-Bearing Puller without hydraulics, Bearing Cup Puller and Bearing Puller may be ordered separately. See items 20, 30 and 40

BHP Series

Capacity:

7, 12, 18 and 25 tons

Maximum Reach:

14.06 - 34.00 inches

Maximum Spread Range:

10.24 - 22.83 inches

Maximum Operating Pressure:

5000 psi



WARNING!

Not all puller components and configurations are rated at the set capacity. Please contact Enerpac for specific details.

Cross Bearing Puller Sets					
	#	4	100		
Hand Pump	XA11G Air Pump	PUD1300 Electric Pump	XC1201M Cordless Pump		
BHP162	BHP162A	BHP162EB *	BHP162CB *		
BHP261G	BHP261GA	BHP261GEB *	BHP261GCB *		
BHP361G	BHP361GA	BHP361GEB *	BHP361GCB *		
BHP561G	BHP561GA	BHP561GEB *	BHP561GCB *		

EB for 115 V application **EE** for 230 V application

▼ SELECTION CHART - Each set includes all items in columns*

o an itorno iri ociariiri	<u> </u>	EE IOI 230 V application			
	7 ton	12 ton	18 ton	25 ton	
* SET Model Number ▶			BHP361G	BHP561G	
set weight ▶	57 lbs	137 lbs	267 lbs	408 lbs	
	P142	P392	P392	P80	
	RWH121900	RCH202	RCH302	RCH603	
	_	HP2015	HP3015	HP5016	
	HC7206C	HC7206C	HC7206C	HC7206C	
Gauge			GA45GC	GA45GC	
Model Number ►	BHP1772	BHP262	BHP362	BHP562	
Maximum	10.24	13.58	17.32	22.83	
Minimum	4.53	5.51	7.09	8.66	
Maximum	14.06	22.44	27.95	34.00	
Diameter	3/4"-16 UNF	1"-8 unc	11/4"-7 UNC	1%"-5.50 UNS	
Length	15.75	26.38	31.10	38.39	
Length	4.17	4.53	8.07	23.98	
Length	14.06	9.45	18.11	34.02	
Length	_	16.54	27.95	_	
Length	_	22.44	_	_	
Thread	3/4"-16 UNF	3/4"-16 UNF	1"-14 uns	11/4"-12 UNF	
Thread	5⁄8"-18 UNF	%" -18 ∪NF	1"-14 uns	11/4"-12 UNF	
Model Number ►	BHP180	BHP280	BHP380	BHP580	
Model Number ►	BHP181	BHP282	BHP382	BHP582	
Model Number ▶	CW166	CW166	CW550	CW750	
	T Model Number ► set weight ► Model Number ► Maximum Minimum Maximum Diameter Length Length Length Length Thread Thread Model Number ► Model Number ►	T Model Number ► 57 lbs set weight ► 57 lbs P142 RWH121900 HC7206C GA45GC Model Number ► BHP1772 Maximum 10.24 Minimum 4.53 Maximum 14.06 Diameter ¾4"-16 unF Length 15.75 Length 14.06 Length - Length - Length - Thread ¾4"-16 unF Thread ¾4"-16 unF Thread ¾4"-18 unF Model Number ► BHP180 Model Number ► BHP181	T Model Number ► BHP162 BHP261G set weight ► 57 lbs 137 lbs P142 P392 RWH121900 RCH202 - HP2015 HC7206C HC7206C GA45GC GA45GC Model Number ► BHP1772 BHP262 Maximum 10.24 13.58 Minimum 4.53 5.51 Maximum 14.06 22.44 Diameter ¾"-16 UNF 1"-8 UNC Length 15.75 26.38 Length 4.17 4.53 Length 14.06 9.45 Length 14.06 9.45 Length - 16.54 Length - 16.54 Length - 22.44 Thread ¾"-16 UNF ¾"-16 UNF Thread 5%"-18 UNF 5%"-18 UNF Model Number ► BHP180 BHP280 Model Number ► BHP181 BHP282	T Model Number BHP162 BHP261G BHP361G set weight 57 lbs 137 lbs 267 lbs P142 P392 P392 RWH121900 RCH202 RCH302 HP2015 HP3015 HC7206C HC7206C HC7206C GA45GC GA45GC GA45GC Maximum 10.24 13.58 17.32 Minimum 4.53 5.51 7.09 Maximum 14.06 22.44 27.95 Diameter ¾"-16 UNF 1"-8 UNC 11¼"-7 UNC Length 4.17 4.53 8.07 Length 4.17 4.53 8.07 Length - 16.54 27.95 Length - 22.44 - Thread ¾"-16 UNF ¾"-16 UNF 1"-14 UNS Thread ¾"-16 UNF ½"-18 UNF 1"-14 UNS Model Number BHP180 BHP280 BHP380 Model Number BHP181 BHP282 BHP382	

^{*} Each set includes Cross-Bearing Puller, Bearing Cup Puller, Bearing Separator and Case