▼ Shown: **HF95T, HF95X, HF95Y**



- Maximum pump volumetric efficiency
- Maximum internal heat transfer
- Prevents pump cavitation
- Additives prevent rust, oxidation and sludge
- · High viscosity index
- Maximum film protective lubricity.

The Genuine Range

Hydraulic Oil

Contents	Model Number	Use only genuine Enerpac Hydraulic Oil.
1 litre	HF95X	The use of any other fluid
5 litres	HF95Y	will render your Enerpac warranty null and void.
20 litres	HF95T	warranty hall and volu.

▼ OIL SPECIFICATION CHART

Viscocity Index	100 min
Viscocity (cSt @ 40 °C)	32
API Gravity	31-33
Density (cSt @ 15 °C)	875
Flash point	204 °C
Pour point	-32 °C
Colour	Blue
Working Temperature Range	0 - 60 °C
Ideal working temperature	40 °C

700 bar Manifolds

Description		Model Number	Dimensions (mm)	
7-port Manifold, short	•	A64	3/8"- 76 50 3/8"- 203 83 18NPTF (7x) 6,3 89 184	_
7-port Manifold, long allows direct mounting of control valves to the manifold.	2000	A65	32 32 38 38 38 32 32 102 102 102 102 3 178 369	2
6-port Manifold, hexagon Plugs furnished for all ports	2	A66	A64 A65	
3%"-18 NPTF.			58 1/4"-20UNC 3/8"-18NPTF (6x)	
Control Manifolds * For control of two or four single- acting cylinders simultaneously.	TITT	AM21	90 12.7 07.1 07.1 07.1 07.1 07.1 07.1 07.1 07	
AM21 with 5 ports %"NPTF. AM41 with 7 ports %"NPTF.		AM41	8 5 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	

^{*} See page 142 for AMGC-Series 4-way manifold assembly complete with gauges.